

## PRODUCT DESCRIPTION

BF PRINTREFLEX is a reflective heat transfer film, printable with solvent, eco-solvent and latex inks, suitable for heat transfer on cotton fabrics, polyester and acrylic garments.

Thanks to its opacity BF PRINTREFLEX can be used on both light and dark garments and can be pressed on T-shirts, sportswear or uniforms for work.

## APPLICATION STEPS

- Print - do not mirror
- Cut - 60° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 150°C/305°F
- Place your graphic on the shirt
- Press it - 150°C/305°F for 10 seconds
- Wait 6/7 seconds
- Remove BF MYLAR - semi-hot

## SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt
H 75 cm	/
H 100 cm	/
H 150 cm	/

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev\_2021/03

## TECHNICAL DATA



Film: PU/polyurethane



Thickness: 150μ (±5%)



Liner: adhesive PET



Finish: reflex



Inks: solvent, eco-solvent, latex

## PLOTTER SETTING



Cut settings: do not mirror



Blade: 60°



Minimum cut: 1 cm

## APPLICATION



Temperature: 150°C - 305°F



Time: 10''



Liner removal: semi-hot,  
wait 6/7 seconds



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed,  
nylon and treated fabrics

## WASH RESISTANCE

First wash after application wait 12 hours

Max wash temperature\* 40°C - 104°F

Dry clean

Dryer

\*Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

**BF PRINTREFLEX**

**PRINT&CUT**



- Reflective effect
- Pleasant and soft on any garment
- Washing resistant and durable