

# HP Scitex XL1500

High-speed super-wide format digital printing system



The HP Scitex XL1500 opens a clear path to super-wide printing success. It delivers a unique combination of high productivity and performance, cost effective production, and superb print quality - in short, all the key elements needed for rapid return on investment.

You can achieve high-quality output at speeds of up to 60 sqm/hr (646 sqft/hr). Or, you can opt for draft mode for long-distance view applications and race ahead at up to 124 sqm/hr (1,333 sqft/hr). With the HP Scitex XL1500 you can print almost any application, in almost any size, format or media, double-sided or backlit.

## Key features

### Dedicated Onyx® PosterShop® RIP

- Market-leading RIP for 4, 6 and 8-color systems, optimized for the HP Scitex XL1500
- Enhanced color management (saturation, gray levels, color replacement)
- Option to work in parallel, enabling a file to undergo RIP while the operator works on the next file
- Supports TIFF, EPS, PS, JPEG, PhotoShop, and more

### Maximum productivity

- High quality-to-speed ratio
- Load file while printing feature
- High speed: up to 124 sqm/hr/1,333 sqft/hr
- Multi-roll (printing up to 3 rolls simultaneously)
- Free-fall option
- Skip white feature

### Integrated drying system

Strong, versatile and fully controllable drying mechanism based on infrared (IR) devices.

### Print head carriage

Advanced head carriage structure provides high fire frequency and enables high-quality results.

### Superb quality in multiple modes

- Optimized modes for high quality or high production
- 4, 6 or 8 colors
- Up to 370 x 740dpi
- HP Supertext

### 8 ink colors

Dedicated HP Scitex XL300 Supreme inks enable optimized usage of your printer and consistent production. They offer an extended color gamut, deliver a smooth appearance and dry completely, even in heavily loaded double-sided blockouts.

### Almost any media - from standard to high-profit

- Canvas, mesh, flexface banner, self-adhesive vinyl, fabrics, carpet, paper and more
- Any width and any length, in virtually any thickness
- Large variety of recommended media

### Dedicated applications

- Building coverings
- Flexface billboards
- Backlit indoor and outdoor signage
- Double-sided applications
- Exhibition and event banners
- Popup displays
- Truck-side curtains
- Textiles, including carpets



# Product specifications

<b>Technology</b>	Drop-on-demand, piezoelectric inkjet, 8 - color: C, M, Y, K, LC, LM, LY, LK process* Switchable between 4, 6 and 8 color process*
<b>Resolution (max)</b>	370 x 740dpi**
<b>Print size (max)</b>	<b>Width:</b> XL1500 5 - 5m/16.4ft XL1500 3 - 3.2m/10.5ft XL1500 2 - 2.2m/7.2ft <b>Length:</b> media roll
<b>Speeds (max)</b>	XL1500 5 - 124 sqm/hr/1333 sqft/hr XL1500 3 - 118 sqm/hr/1268 sqft/hr XL1500 2 - 105 sqm/hr/1129 sqft/hr
<b>Media</b>	<b>Width (max):</b> HP Scitex XL1500 5 - 5.2m/17ft HP Scitex XL1500 3 - 3.4m/11.2ft HP Scitex XL1500 2 - 2.4m/7.9ft <b>Handling:</b> Roll-to-roll or roll-to-sheet printing <b>Types:</b> Self-adhesive vinyl, PVC, mesh, fabrics, flexface banner, paper and more
<b>Ink</b>	Ink series HP Scitex XL300 Supreme Pigment and solvent-based. Supreme ink is UV-durable for up to 2 years***
<b>RIP</b>	Onyx® dedicated RIP <b>Input:</b> All popular graphic file formats, including: EPS, PostScript level 3 and PDF
<b>Output</b>	<b>TIFF PPI:</b> resolution 5 - 23dpi <b>TIFF bitmap (pre-separated):</b> resolution 46 - 370dpi
<b>Control station</b>	<b>Interface:</b> Network (Ethernet, TCP/IP), CD <b>Hardware:</b> Pentium IV, 512Mb RAM, 2.4GHz, 533MHz (512K), 36Gb hard disk, 15" flat screen, network card <b>Software:</b> Dedicated HP Scitex XL1500 software, Windows 2000 compatible
<b>Operating requirements</b>	<b>Electrical voltage:</b> 220 - 240V, Ph, 50/60Hz, 63A per phase/110 - 120V, 3Ph, 60Hz, 63A per phase <b>Power consumption:</b> 30KVA (max) <b>Air pressure:</b> 6 - 8atm
<b>Operating environment</b>	<b>Temperature:</b> 20 - 25°C/68 - 77°F <b>Humidity:</b> 40 - 70% non condensing
<b>Physical characteristics</b>	<b>Size (HWD):</b> XL1500 5 - 2 x 6.5 x 1.5m/6.7 x 21.3 x 4.9ft XL1500 3 - 2 x 4.7 x 1.5m/6.7 x 15.4 x 4.9ft XL1500 2 - 2 x 3.6 x 1.5m/6.7 x 11.8 x 4.9ft <b>Weight (net):</b> XL1500 5 - 3700kg/8222lbs XL1500 3 - 2900kg/6444lbs XL1500 2 - 2300kg/5111lbs
<b>Special features</b>	Switch between 4, 6 and 8 colors and back • Load file while printing • Sample mode - sharp 8 point text • Multi-roll handling • Backlit and double-sided printing • Skip white • HP Supertext

\* Only available in HP Scitex XL1500 3m

\*\* Apparent in XL quality mode and sample mode

\*\*\* According to standard ASTM-D2565-99

© 2006 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.  
399000324, 05/2006

[www.hp.com/go/scitex](http://www.hp.com/go/scitex)  
[info.scitex@hp.com](mailto:info.scitex@hp.com)

