BF GLOW IN THE DARK

CAD CAM



PRODUCT DESCRIPTION

The BF GLOW IN THE DARK series is a photoluminescent polyurethane film, free of PVC, plasticizers or heavy metals, created to bright in the dark!

The cutting line of all the films is highly visible and the workability of the product is unique; its polyester adhesive carrier allows for fast weeding and easy repositioning of any small details that might have accidentally lifted from the carrier.

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 130μ (±5%)



Liner: adhesive PET



Finish: matte

APPLICATION TECHNIQUES

- Knockout
- Layering with other series

PLOTTER SETTING



Cut settings: mirror



Blade: 45°



Minimum cut: 0,5 cm

APPLICATION STEPS

- Cut 45° blade
- Weed excess material
- Turn on your heat press heat to 145°C/295°F
- Place your graphic on the garment
- Press it 145°C/295°F for 12 seconds
- Wait 6/7 seconds
- Remove the liner semi-hot

APPLICATION



Temperature: 145°C - 295°F



Time: 12"



Liner removal: semi-hot

wait 6/7 seconds



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed

SIZES

H 50 cm	L	25 mt / 10mt / 5 mt / 1 mt
H 75 cm	L	25 mt (upon request)
H 100 cm	L	25 mt (upon request)
H 150 cm	L	25 mt (upon request)

Comply with regulation REACH n°1907/2006/EU

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	40°C - 104°F
Dry clean	×
Dryer	low

SAFETY NOTICE

HEADOUARTERS

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03

follow us













B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

BF GLOW IN THE DARK



COLOUR GUIDE



- Photoluminescent effect
- Easy to work
- Washable up to 40°C



GLOW IN THE DARI

