



**B-FLEX ITALIA S.r.l.**

Via 1° Maggio, 44  
36050 Sovizzo (VI) ITALY  
Ph +39 0444.028139  
info@b-flexitalia.com

[www.b-flexitalia.com](http://www.b-flexitalia.com)

follow us on



**BF GLAM**



## BF GLAM

### PRODUCT DESCRIPTION

The BF GLAM SERIES is composed of special thermo-adhesive films coated with glossy polyester (PET) foil with a holographic finishing, free of PVC, plasticizers or heavy metals.

The cutting lines are highly visible, and the workability of the product is simple; its polyester adhesive carrier allows for fast weeding and easy repositioning of any small details that might have accidentally lifted from the carrier.

The blade integrity of the cutting plotter significantly determines the workability of the film.

It is not suitable for multilayer applications.

### APPLICATION INSTRUCTIONS

- Mirror cut BF GLAM, with a 60° blade.
- Weed the BF GLAM and remove the excess materials.
- Pre-heat your press to 140 ° C.
- Place the garment on the lower platen of your heat press.
- Place your BF GLAM design on the garment.
- Press at 140 ° C for 12 seconds.
- Peel the carrier

### STANDARD SIZES

- H 150 cm => available lengths:  
not available
- H 100 cm => available lengths:  
not available
- H 75 cm => available lengths:  
not available
- H 50 cm => available lengths:  
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

### APPLICATION TIPS

- Recommended Fibers: organic, synthetic, mixed.
- Not recommended for layering.
- Can be applied with other B\_FLEX films (ex. FATTY, GLITTER, FLOCK, etc.) .
- Ability to cut designs as small as 0.3 cm.
- Doesn't require a Teflon sheet during the pressing phase.
- Do not spin after washing.

### TECHNICAL DATA

Film:	PET / Poliestere
Carrier:	PET film – self adhesive

### APPLICATION

Temperature:	140°C - 285° F
Time:	12"
Pressure:	medium – 3,5 bar – 50 PSI

### LINER REMOVAL

Hot

### WASH RESISTANCE

First wash:	wait 12 hours after application
Max. Wash temp.:	40° C
Dry clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

### SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:  
BF GLAM. Rev\_2019/09\_EN