BF SUBLISTOP80 CAD CAM



PRODUCT DESCRIPTION

BF SUBLISTOP80 was developed to be applied on sublimated polyester garments. With a thickenss of just 80 microns, we added a built-in blocker to the polyurethane film to stop the dye migration process. This product can withstand multiple wash cycles. Thanks to the highly visible cutting lines and the ease of use, you can rest assured that this product will increase your productivity.

BF SUBLISTOP80 features a thinkness of only 80 microns. It can also be layered and can withstand wash cycles up to 40° C.

APPLICATION TECHNIQUES

- Knockout
- Layering from other series

APPLICATION STEPS

- Cut 45° blade •
- Weed excess material
- Turn on your heat press heat to 130°C/265°F •
- Place your graphic on the garment •
- Press it 130°C/265°F for 8 seconds •
- Remove the liner hot

SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt / 1 mt
H 75 cm	L 25 mt (upon request)
H 100 cm	L 25 mt (upon request)
H 150 cm	L 25 mt (upon request)

Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA



Thickness: 80µ (±5%)

- Liner: adhesive PET
- Finish: opaque

PLOTTER SETTING



Blade: 45°



Minimum cut: 0,5 cm

Cut settings: mirror

APPLICATION

follow us

Temperature: 130°C - 265°F Time: 8" Liner removal: hot Pressure: medium - 3,5 bar - 50 PSI Textile: synthetic, sublimated fabrics

WASH RESISTANCE

wait 12 hours
40°C - 104°F
×
×

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03

BF SUBLISTOP80



COLOUR GUIDE

Ultra thin!

- Prevents the color's pigmentations from migrating from the fabric to the film's surface
- Fully opaque



WHITE SUBLISTOP (80µ)

