BF PRINT03 PRINT&CUT



PRODUCT DESCRIPTION

BF PRINT03 is a mix of polyurethane and PVC (50%+50%) white opaque film printable with solvent, eco-solvent and latex inks. BFPRINT03 is suitable for heat transfer on cotton fabrics, polyester and acrylic garments. Thanks to its self-adhesive carrier, the film can be easily cut by all current cutting plotters after the printing process and because of its thickness can be removed and places on all garments by hand without liner.

Alternatively, if preferred, we suggest to use the BF MYLAR film as a transfer tape and then remove it while hot.

APPLICATION STEPS

- Print do not mirror •
- Cut 45° blade
- Weed excess material
- Apply BF MYLAR remove air bubbles •
- Remove from liner •
- Turn on your heat press - heat to 145°C/295°F
- Place your graphic on the shirt .
- Press it 145°C/295°F for 12 seconds •
- Remove BF MYLAR hot

SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt	
H 75 cm	L 25 mt (upon request)	
H 100 cm	L 25 mt (upon request)	
H 150 cm	L 25 mt (upon request)	

OEKO-TEX®

Tested for harmful substances ww.oeko-tex.com/standard100

Oeko-Tex Standard 100 Class I



TECHNICAL DATA

	Film: 50% PU/Polyurethane 50% PVC
μ	Thickness: 120µ (±5%)
\triangleright	Liner: adhesive PET
	Finish: opaque
•	

Inks: solvent, eco-solvent, latex

PLOTTER SETTING

ଚାର Cut settings: do not mirror

Blade: 45°

Time: 12"

Minimum cut: 2 cm

APPLICATION

Temperature: 145°C - 295°F

Liner removal: hot

Pressure: medium - 3,5 bar - 50 PSI

Textile: organic, synthetic, mixed

WASH RESISTANCE

First wash after application	wait 12 hours	
Max wash temperature*	40°C - 104°F	
Dry clean	×	
Dryer	×	

stTemperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in Rev_2021/03 this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.



HEADOUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com www.b-flexamerica.com ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com www.b-flexpacific.com



BF PRINTO3 PRINT&CUT

0 1987

- Suitable for garments subject to high wear such as workwear
- This film can also be transferred without any application tape
- For smoother fabrics