



B-FLEX ITALIA S.r.l.

Via 1° Maggio, 44
36050 Sovizzo (VI) ITALY
Ph +39 0444.028139
info@b-flexitalia.com

www.b-flexitalia.com

follow us on



BF METTALLIC



BF METALLIC

PRODUCT DESCRIPTION

BF METALLIC series consists of 4 polyurethane films characterized by a pearlescent finishing with an iridescent effect.

The cutting line of all the films is highly visible and the workability of the product is unique; its polyester adhesive carrier allows for fast weeding and easy repositioning of any small details that might have accidentally lifted from the carrier.

The BF METALLIC series is suitable for multilayer applications and is resistant to washing up to 40°C. The colors available allow it to be used for application on sporty and fashion clothing.

APPLICATION INSTRUCTIONS

- Mirros cut BF METALLIC with a 45° blade.
- Weed BF METALLIC and remove all excess material.
- Pre-heat your press to 140°C.
- Place the garment on lower platen of your heat press.
- Place your BF METALLIC design on the garment.
- Press at 140 ° C for 12 seconds.
- Peel the carrier.

STANDARD SIZES

- H 150 cm => available lengths:
25 mt (upon request)
- H 100 cm => available lengths:
25 mt (upon request)
- H 75 cm => available lengths:
25 mt (upon request)
- H 50 cm => available lengths:
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

APPLICATION TIPS

- Recommended fibers: organic, synthetic, mixed.
- Ideal for layering
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc) .
- Ability to cut design as small as 0.25 cm
- Doesn't require a Teflon sheet during the pressing phase.

TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	90 μ (±5%)
Carrier:	PET film – self adhesive

APPLICATION

Temperature:	140°C - 285° F
Time:	12"
Pressure:	medium – 3,5 bar – 50 PSI

LINER REMOVAL

Hot

WASH RESISTANCE

First wash:	wait 12 hours after application
Max. wash Temp.:	40° C
Dry clean:	YES
Softener:	YES
Bleach:	YES
Dryer:	YES

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:
BF METALLIC. Rev_2019/09_EN