



BF MIRROR

PRODUCT DESCRIPTION

The BF MIRROR SERIES is a special thermo-adhesive film covered by a very glossy polyester sheet (PET), free of PVC, plasticizers or heavy metals, which gives a total mirrored effect EVEN AFTER THE APPLICATION thanks to its rigid conformation.

The cutting line is highly visible, and the workability of the product is simple; its polyester adhesive carrier allows for fast weeding and easy repositioning of any small details that might have accidentally lifted from the carrier. The cutting plotters blade integrity significantly determines the workability of the film.

It is not suitable for multilayer applications.

APPLICATION INSTRUCTIONS

- Mirror cut BF MIRROR, with a 45° blade.
- Weed the BF MIRROR and remove the excess materials.
- Pre-heat your press to 150°C.
- Placethe garment on the lower platen of your heat press.
- Place the your BF MIRROR design on the garment.
- Press at 150°C for 12 seconds.
- Wait 5-7 seconds before peeling the carrier.

STANDARD SIZES

- H 150 cm => available lenghts: not available
- H 100 cm => available lenghts: not available
- H 75 cm => available lenghts: not available
- H 50 cm => available lenghts:25 mt / 12,5 mt / 5 mt / 1 mt (standard)

APPLICATION TIPS

- Recommended fibers: organic, synthetic, mixed.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc.).
- Ability to cut design as small as 0.25 cm
- Doesn't require a Teflon sheet during the pressing phase.
- No spin after washing

TECHNICAL DATA

Film: PET / poliestere Thickness: $140 \mu (\pm 5\%)$

Carrier: PET film – self adhesive

APPLICATION

Temperature: 150°C - 305° F

Time: 12"

Pressure: medium – 3,5 bar – 50 PSI

LINER REMOVAL

Warm; wait 5-7 seconds after the application

WASH RESISTANCE

First wash: wait 12 hours after application

Max wash Temp.: 30°C
Dry clean: NO
Softener: NO
Bleach: NO
Dryer: NO

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products: BF MIRROR. Rev_2019/09_EN