BF PRINTFATTY
BF PRINTFATTYUV

B-FLEX HEAT TRANSFER VINYL

PRINT&CUT

PRODUCT DESCRIPTION

BF PRINTFATTY is a polyurethane heat transfer film printable with solvent, eco-solvent and latex based inks, suitable for heat transfer on any fabric.
Thanks to its sticky carrier small letters and drawings can be easily cut by all current cutting plotters after the printing process. BF PRINTFATTY can be pressed on t-shirts and sportswear or uniforms for work and is ideal for small logos or drawings to add extra dimension to the garments.

BF PRINTFATTYUV is the version of the BF PRINTFATTY film compatible with UV printers. This allows the inks to dry immediatly, eliminating waiting times.

TECHNICAL DATA

- Film: PU/polyurethane
- Thickness: 750µ (±5%)
- Liner: adhesive PET
- Finish: opaque
- Inks:
  BF PRINTFATTY: solvent, eco-solvent, latex
  BF PRINTFATTYUV: UV inks

PLOTTER SETTING

- Cut settings: do not mirror
- Blade: 60°
- Minimum cut: 2 cm

APPLICATION

- Temperature: 150°C - 305°F
- Time: 15''
- Liner removal: hot
- Pressure: medium-low - 2,0 bar - 30 PSI
- Textile: organic, synthetic, mixed

APPLICATION STEPS

- Print - do not mirror
- Cut - 60° blade
- Weed excess material
- Apply BF MYLAR - remove air bubbles
- Remove from liner
- Turn on your heat press - heat to 150°C/305°F
- Place your graphic on the shirt
- Press it - 150°C/305°F for 15 seconds
- Remove BF MYLAR - hot

SIZES

H 50 cm	*L*	*10 mt / 5 mt / 2,5 mt*
H 75 cm		/
H 100 cm		/
H 150 cm		/

WASH RESISTANCE

First wash after application	*wait 12 hours*
*Max wash temperature**	*40°C - 104°F*
Dry clean	✗
Dryer	✗

**Temperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.*

Oeko-Tex Standard 100 Class I

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 19CX00033 CENTROCOT Tested for harmful substances. www.oeko-tex.com/standard100

*Comply with regulation **REACH n°1907/2006/EU***

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. *Rev_2021/03*

follow us

HEADQUARTERS **B-FLEX ITALIA S.r.l.** info@b-flexitalia.com | www.b-flexitalia.com
NORTH AMERICA BRANCH **B-FLEX AMERICA LLC** info@b-flexamerica.com | www.b-flexamerica.com
ASIA-PACIFIC BRANCH **B-FLEX PACIFIC PTY LTD** info@b-flexpacific.com | www.b-flexpacific.com

B-FLEX
HEAT TRANSFER VINYL

BF PRINTFATTY - BF PRINTFATTYUV

PRINT&CUT



- *3-D effect*
- *Suggested for fabrics with smooth surfaces*
- *Also available for UV printers*

B-FLEX ITALIA S.r.l. | Via 1° Maggio, 44 | 36050 Sovizzo (VI) ITALY | Ph +39 0444.028139 | info@b-flexitalia.com | www.b-flexitalia.com