# **BF PRINTTOPM-G**

PRINT&CUT



## PRODUCT DESCRIPTION

BF PRINTTOPG (glossy) and BF PRINTTOPM (matte) are two thin polyurethane white films printable with solvent, eco-solvent and latex inks and are suitable for heat transfer on cotton fabrics, polyester, nylon Lycra and acrylic garments.

Available two BF PRINTTOP version:

- BF PRINTTOPM-G/P WITH PAPER BACKING: not adhesive, really easy to transfer;
- BF PRINTTOPM-G WITH PET BACKING: adhesive, stability during printing.

We recommend the BF MYLAR film as a transfer tape and as a protection during the heat transfer, and then remove it while hot.

## **APPLICATION STEPS**

- Print do not mirror
- Cut 45° blade
- Weed excess material
- Apply BF MYLAR remove air bubbles
- Remove from liner
- Turn on your heat press heat to 145°C/295°F
- Place your graphic on the shirt
- Press it 145°C/295°F for 8 seconds
- Remove BF MYLAR hot

#### SIZES

H 50 cm	L 25 mt / 12,5 mt / 5 mt
H 75 cm	L 25 mt (upon request)
H 100 cm	L 25 mt (upon request)
H 150 cm	L 25 mt (upon request)

Oeko-Tex Standard 100 Class I



Comply with regulation REACH n°1907/2006/EU

B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

#### **TECHNICAL DATA**



Film: PU/polyurethane



Thickness: 60µ (±5%)



Liner: adhesive PET

available also in paper (P)



Finish: BF PRINTTOPM opaque BF PRINTTOPG glossy



Inks: solvent, eco-solvent, latex

# **PLOTTER SETTING**



Cut settings: do not mirror



Blade: 45°



Minimum cut: 1 cm

#### **APPLICATION**



Temperature: 145°C - 295°F



Time: 8"



RLiner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: organic, synthetic, mixed, nylon,

treated fabrics

# **WASH RESISTANCE**

First wash after application	12 hours
Max temperature*	40°C - 104°F
Dry clean	×
Dryer	X

stTemperatures related on heat transfer vinyl; for the inks features, refer to the data sheet inks producer's.

#### SAFETY NOTICE

**HEADOUARTERS** 

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev\_2021/03

follow us















# **BF PRINTTOPM-G PRINT&CUT** Soft touch Stronger adhesive to perform on treated or coated fabrics Available also with liner in paper